



ODORLESS MINERAL SPIRITS

	<u>SPECIFICATIONS</u>	<u>TYPICAL*</u>
Specific Gravity at 60°F (D-891)	0.740 - 0.775	0.7603
Color, Saybolt (D-156)	30 min	+ 30
Color, Pt-Co (D-1209)		< 15
Flash Point, °F (D-56)	110 min (43°C)	124 (51°C)
Kauri-Butanol Value (D-1133)		28
Corrosion (D-130)		1A
Distillation, °F (D-86)		
IBP	340 min (171.0 °C)	347 (175.0 °C)
Dry Point	410 max (210.0 °C)	392 (200.0 °C)
Aromatic content		< 0.25 vol %

SHIPPING DATA:

Pounds per Gallon, 60°F(15.6°C)	6.33
Kg per Liter, 60°F (15.6°C)	0.76
Flash Point, °F (T.C.C.)	124 (51°C)
DOT Label Required	None
DOT Identification No.	UN 1268

Odorless Mineral Spirits meets the following specifications:

ASTM D-235 (Type III) Mineral Spirits

TT-T-291F (Type III) Thinner, Paint, Mineral Spirits, Regular and Odorless (S/S by A-A-2904)

A-A-2904 Thinner, Paint, Mineral Spirits, Regular and Odorless (S/S by MIL-PRF-680C)

MIL-PRF-680C (Type I) Degreasing Solvent, Mineral Spirits, Low Flash Point

The specifications on this sheet are provided by the manufacturer. We do not guarantee the accuracy of these specifications as they are subject to change without notice.