



Purecool Extended Life Antifreeze/Coolant

STARFIRE PURECOOL EXTENDED LIFE ANTIFREEZE/COOLANT is a premium, virgin, ethylene glycol-based product that may be used in all GM® vehicles that require DEX-COOL® coolant, as well as other cars and light duty trucks with aluminum radiators.

STARFIRE Purecool Extended Life Antifreeze/Coolant when used as directed:

- Meets GM6277M, ASTM D 3306 and ASTM D 4985
- May be added to conventional antifreeze/coolant
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications
- DEX-COOL® is a registered trademark of GM Corporation
- Available in concentrate and 50/50 prediluted formulas



| PURECOOL | TYPICAL VALUES | ASTM METHOD |
|---|----------------|-------------|
| Ash Content (50% by Volume Solution) | 1.5% by weight | D1119 |
| pH 50% by Vol. Solution | 10.0 – 11.0 | D1287 |
| Reserve Alkalinity | 2.4 | D1121 |
| Specific Gravity at 20/20°C (50% by Volume Solution) | 1.064 | D1122 |
| Freezing Point (50% by Volume Solution) | -34 | D1177 |
| Boiling Point (50% by Volume Solution) | 227°F | D1120 |
| Flash Point (Tag Open Cup) (70% by Volume Solution) | None | |
| Foam Test | 50mL/2.0 sec. | D1881 |
| Color | Orange | |