

STARFIRE®

PREMIUM LUBRICANTS

DEXRON®-VI Low Viscosity ATF

STARFIRE DEXRON®-VI LOW VISCOSITY AUTOMATIC TRANSMISSION FLUID is a full synthetic, high quality fluid designed to meet the specific requirements of General Motors automatic transmissions calling for DEXRON®-VI fluid. This high-quality product is also suitable for use where DEXRON®-II, DEXRON®-III, JASO M315(1A), Mercon® SP, Toyota WS, or Toyota T-IV fluids are recommended.

BENEFITS

- Full Synthetic
- GM Approved
- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures
- Friction stability to maintain smooth consistent shift performance

CLAIMS INFORMATION

Type A*

Dexron VI***

Audi G 052 025, 052 162, 055 025*

BMW 7045E, LA2634, LT71141*

Dexron III, Dexron II, Dexron*

Honda DW-1, Z-1*

Hyundai/Kia SP-II and SP-III*

Hyundai SP-IV*

JWS 3309*

M315-2004 JASO 1A*

M315-2004 JASO 2A*

MAN 339 Type Z1, V1*

MAN 339 Type Z2*

MAN 339 Type V2

Mazda ATF M-III, MV*

NAG-1*

MB 223.2, 236.1, 236.10, 236.12, 236.41,
236.5, 236.6, 236.7, 23*

Mercon V (XT-5-QM, XT-5-DM)**

Mercon, Ford ESP-M2C166-H**

Mercon SP, except 6HP26 / 6R60/ 6R75
transmissions**

XT-6-QSP, XT-6-DSP, except 6HP26 /
6R60/ 6R75 transmissions**

Mercon LV (XT-10-QLV)***

Mitsubishi Diamond SP-II, SP-III, J2*

Nissan Matic-D, J, K, 402*

Nissan Matic, J, S*

Shell 3403, LA2634, Texaco 7045-E,
ETL-8072B*

Subaru ATF, ATF-HP*

Toyota T-III, T-IV, WS, Ford XT8QAW*

JWS 3309*

Volvo Passenger Car (4 – 6 sp),
Volvo 97340, 97341*

VW G 052 025, 162, 099, 055 025*

ZF TE-ML 02F, TE-ML 03D,
TE-ML 04D, TE-ML 09, TE-ML 11A

ZF TE-ML 14A, TE-ML 14B,

TE-ML 14C, TE-ML 16L,

ZF TE-ML 17C*

VW TL52162 (LT71141)*

* Suitable for Use

** Vis Requirements not met

*** Approved



TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	28.56
cSt @ 100°C	5.797
Viscosity Index	151
Pour Point, °F	-60
Specific Gravity @ 60°F (15.6°C)	0.8468
Gravity, °API	35.6
Color	Red