

STARFIRE®

PREMIUM LUBRICANTS

MERCON® V ATF

STARFIRE MERCON® V ATF is specially formulated with a unique combination of conventional base stocks and advanced additive technology to meet performance requirements of Ford automatic transmissions calling for MERCON® V fluid. Not for use in transmissions requiring Ford Type F fluid or Continuous Variable Transmissions (CVTs).

STARFIRE MERCON® V ATF is suitable for use where the following automatic transmission fluids are recommended: automobile and truck automatic transmissions, power-shift transmissions and other types of service requiring an approved and Ford Mercon® V automatic transmission fluid. Dexron®-III (G, H), II (E, F) specifications, Honda Z-1, Nissan Matic-J and Toyota T-IV.

CLAIMS INFORMATION

Allison C-4***
 Allison TES-389*
 Audi G 052 025, 052 162, 055 025*
 Esso 71141*
 BMW P/N 83 22 0 024 359, ETL-8072B*
 BMW P/N 83 22 0 0246 922, ETL-7045E*
 BMW P/N 83 22 0 403 249, ETL-8072B*
 BMW P/N 83 22 9 407 765, LA 2634*
 BMW P/N 83 22 9 407 807, LT 711 41*
 BMW 7045E, LA2634, LT71141*
 Dexron III G/H, Dexron II,
 Dexron, AW1*
 Honda DW-1, Z-1*
 Volvo P/N 1161540-8*
 Hyundai/Kia/Mitsubishi Diamond
 SP-II and SP-III, RED-1, SP-IV*
 Chrysler AS68RC, Diamond SP-III*
 Idemitsu K17*
 JWS 3309, Any 3309*
 M315-2004 JASO 1A, 2A***
 MAN 339 Type Z1, Z2, V1**
 Mazda ATF M-III, MV, T-IV*
 MB236.1, 2, 5, 6, 7, 9, 10, 11*
 Suzuki 3314, 3317*
 Ford P/N XT-2-DX (MERC),
 Ford P/N XT-2-SM (SYN MERC)*
 Mercon V (XT-5-QM, XT-5-DM)***
 Mercon, Ford ESP-M2C166-H*
 Nissan Matic-D, J, K, 402*
 Texaco N402*
 Shell 3403, LA2634,
 Texaco 7045-E, ETL-8072B*

Hyundai NSWS9638*
 Fuchs 3353*
 IDEMITSU APOROIL ATF HP*
 ISUZU 08200-9001 / Genuine ATF*
 MINI P/N 83 22 0 402 413*
 Saturn P/N 21005966*
 SAAB P/N 22 717 466, 93 165 147 (AW-1)*
 Jaguar P/N WSS-M2C922-A-1*
 Porsche P/N 999 917 547 00 (A2)*
 VW P/N GUS 000 162*
 Shell ATF 134, 3353, 3403 M115*
 Subaru ATF, ATF-HP*
 Toyota T-II, T-III, T-IV, WS, Ford XT8QAW*
 Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF*
 JWS 3324*
 Voith 55.6335 (G607)*
 Volvo Passenger Car (4 - 6 sp),
 Volvo 97340, 97341)*
 VW G 052 025, 162, 099, 055 025*
 ZF TE-ML 03D, 04D, 05L, 09, 11B,
 14A, 16L, 17C, ZF TE-ML 14B

* Suitable for Use
 ** Meets Requirements
 *** Approved



TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	35.43
cSt @ 100°C	7.56
cP @ -40°C, max.	13000
Viscosity Index, min.	189
Flash, COC, °F	390
Pour Point,, °F	-60
Specific Gravity @ 60°F	0.8601
API Gravity	33.02
Color	Red