



Purecool Extended Life Antifreeze/Coolant

STARFIRE Purecool Extended Life Antifreeze/Coolant is a premium, virgin, ethylene glycol-based product that may be radiators. used in all GM® vehicles that require DEX-COOL® coolant, as well as other cars and light duty trucks with aluminum

STARFIRE Purecool Extended Life Antifreeze/Coolant when used as directed:

- Meets GM6277M, ASTM D 3306 and ASTM D 4985
- May be added to conventional antifreeze/coolant
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications
- DEX-COOL® is a registered trademark of GM Corporation
- Available in concentrate and 50/50 prediluted formulas

PURECOOL	TYPICAL VALUES	ASTM METHOD
Ash Content (50% by Volume Solution)	1.5% by weight	D1119
pH 50% by Vol. Solution	10.0 – 11.0	D1287
Reserve Alkalinity	2.4	D1121
Specific Gravity at 20/20°C (50% by Volume Solution)	1.064	D1122
Freezing Point (50% by Volume Solution)	-34	D1177
Boiling Point (50% by Volume Solution)	227°F	D1120
Flash Point (Tag Open Cup) (70% by Volume Solution)	None	
Foam Test	50mL/2.0 sec.	D1881
Color	Orange	