



## DEXRON® -VI Low Viscosity ATF

**STARFIRE DEXRON®-VI LOW VISCOSITY AUTOMATIC TRANSMISSION FLUID** is a full synthetic, high quality fluid designed to meet the specific requirements of General Motors automatic transmissions calling for DEXRON®-VI fluid. This high-quality product is also suitable for use where DEXRON®-II, DEXRON®-III, JASO M315(1A), Mercon® SP, Toyota WS, or Toyota T-IV fluids are recommended.

### BENEFITS

- Full Synthetic
- GM Approved
- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures
- Friction stability to maintain smooth consistent shift performance

### CLAIMS INFORMATION

Allison C-3	Honda DW-1, Z-1	Nissan Matic, J, S	XT-6-QSP, XT-6-DSP, except 6HP26 / 6R60/ 6R75 transmissions
Allison C-4	Hyundai/Kia/Mitsubishi Diamond	Opel	ZF all 3 & 4 speed trans.
Allison TES-389	SP-II and SP-III, RED-1, SP-IV	Peugeot ZF 4HP20	ZF TE-ML 02F, TE-ML 03D,
Audi 5 HP LT71141, G 052162-A1/A2, G052025 A2	Hyundai/Kia SP-IV M, RR Dex-II/SP-II, JWS 3314, 9683	Porsche P/N 999 917 547 00 (A2)	TE-ML 04D, TE-ML 09, TE-ML 11A
Audi G 052 025, 052 162, 055 025	Hyundai NSWS9638	Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-VI, JWS 3309	ZF TE-ML 14A, TE-ML 14B, TE-ML 14C, TE-ML 16L, ZF TE-ML 17C
BMW 7045E, LA2634, LT71141	Idemitsu APOROIL ATF HP	Saab P/N 22 717 466, 93 165 147 (AW-1)	
BMW JWS 3309, LA2634, ZF 5HP18FL, 5HP24, 5HP30, Mini	Isuzu BESCO ATF-II, III	Saturn P/N 21005966	
BMW P/N 83 22 0 0246 922, ETL-7045E	Isuzu 08200-9001 / Genuine ATF	Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF	
BMW P/N 83 22 0 024 359, ETL-8072B	Jaguar ATF 3403 M115, LT71141, ZF 5HP24, JLM20238	Scion	
BMW P/N 83 22 0 403 249, ETL-8072B	Jaguar P/N WSS-M2C922-A-1	Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	
BMW P/N 83 22 9 407 765, LA 2634	Jaso M315-2013 1A, 1A-LV, 2A	Shell 3403 M115	
BMW P/N 83 22 9 407 807, LT 711 41	JWS 3309, Any 3309	Subaru ATF 5AT, Dex II, AT OIL 5D06	
CAT TO-2	JWS 3324	Subaru ATF, ATF-HP	
Chrysler AS68RC, Diamond SP-III	Lexus JWS 3309	Suzuki ATF 2326, 2384K, JWS 3309, 3314	
Chrysler P/N 05127382AA, P/N 68043742AA (DEX VI)	M315-2004 JASO 1A, 2A	Texaco N402	
Daewoo LT 71141	MAG-1	Toyota D-II, D-III	
Daihatsu ANMIX ATF D-II, D-III SP	MAN 339 Type V2	Toyota T-II, T-III, T-IV, WS, Ford XT8QAW	
DEXRON® III G/H, DEXRON® II, DEXRON®, AW1	MAN 339 Type Z1, Z2, V1	Type A	
Esso 71141	Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317	Voith 55.6335 (G607)	
Fiat T-VI, JWS 3309	Mazda ATF M-III, MV, T-IV	Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	
Ford FNR5	MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9	Volvo P/N 1161540-8	
Ford M2C138-CJ	MERCON®, Ford ESP-M2C166-H	VW 5 HP ZF5 HP 30, 18FL, 30, 19FL, 24A, G-055-025 A2, TL 521 62	
Ford M2C166H, 138CJ, 922A1, 924A, JWS 3309	Mini Cooper T-IV	VW G 052 025, 162, 099, 055 025	
Fuchs 3353	MINI P/N 83 22 0 402 413	VWP/N GUS 000 162	
FUSO ATF-II, SPIII, A4	Mitsubishi DiaQueen SK, AW, J2, J3, PA	VW TL52162 (LT71141)	
GMN10060	Mopar AS 68RC, JWS 3309		
Hino Blue Ribbon ATF	Nissan Matic-D, J, K		

TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	28.56
cSt @ 100°C	5.797
Viscosity Index	151
Pour Point, °F	-60
Specific Gravity @ 60°F (15.6°C)	0.8468
Gravity, °API	35.6
Color	Red