



Premium Plus 15W40 CJ-4 Engine Oil

STARFIRE Premium Plus 15W40 CJ-4 Engine Oil is formulated using premium quality Group II base stocks and advanced additive technology, to provide the highest levels of equipment protection. STARFIRE Premium Plus 15W40 CJ-4 Engine Oil, with next generation soot control, is recommended for heavy duty diesel engines requiring API CJ-4, Cummins CES 20081, Volvo VDS-3, Mack EON Premium Plus, Caterpillar ECF-3, and Detroit Engine Oil 93K216.

STARFIRE Premium Plus 15W40 CJ-4 Engine Oil is a premium quality, heavy-duty, multi-grade oil for all-season use in diesel or gasoline powered equipment. It can be recommended for service requirements of virtually all diesel and gasoline engine manufactures specifying a 15w40 CJ-4 fluid. It can be recommended for both newer and older engines. Especially designed for today's high-performance, low emissions diesel engine equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filters.

APPLICATIONS

- API CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF, CF-2
- When SN, SL, SJ, SH, SG, SF oils are required
- When a US Military CID A-A-52306 performance level is required
- When MIL-L-210E/F oils performance level is required
- ACEA E5-02, JASO DHD-1, GLOBAL DHD-1
- When GM 4718M/6094M and Ford M2C153-E oils are required
- In all diesel and gasoline engines, including turbo-charged models
- When Detroit Engine Oil is required
- In Caterpillar engines ECF-3
- In Mack engines (EO-N PREMIUM PLUS), PREMIUM PLUS, EO-M Plus, EO-M, EO-L Plus, EO-L, EO-K/2
- In Cummins engines CES 20081, 20077, 20076, 20078,
- In Volvo VDS-3, VDS-2 and VDS engines
- In Caterpillar drive trains TO-2
- When Allison C-3/C-4 fluids are required
- Mercedes Benz MB 228.3

SAE GRADE	15W40
Pour Point, °C	-38
Viscosity @ 40°C, cSt	109.6
Viscosity @ 100°C, cSt	14.7
Viscosity Index	137.7
Cold Crank Simulator, cP	5240 (-20°C)
Density (lb/gal)	7.3
Color	3.7