



DEXRON[®]-VI Low Viscosity ATF

STARFIRE DEXRON[®]-VI LOW VISCOSITY AUTOMATIC TRANSMISSION FLUID is a full synthetic, high quality fluid designed to meet the specific requirements of General Motors automatic transmissions calling for DEXRON[®]-VI fluid. This high-quality product is also suitable for use where DEXRON[®]-II, DEXRON[®]-III, JASO M315(1A), Mercon[®] SP, Toyota WS, or Toyota T-IV fluids are recommended.

BENEFITS

- Full Synthetic
- GM Approved
- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures
- Friction stability to maintain smooth consistent shift performance

CLAIMS INFORMATION

Type A*
 Dexron VI***
 Audi G 052 025, 052 162, 055 025*
 BMW 7045E, LA2634, LT71141*
 Dexron III, Dexron II, Dexron*
 Honda DW-1, Z-1*
 Hyundai/Kia SP-II and SP-III*
 Hyundai SP-IV*
 JWS 3309*
 M315-2004 JASO 1A*
 M315-2004 JASO 2A*
 MAN 339 Type Z1, V1*
 MAN 339 Type Z2*

MAN 339 Type V2
 Mazda ATF M-III, MV*
 NAG-1*
 MB 223.2, 236.1, 236.10, 236.12, 236.41,
 236.5, 236.6, 236.7, 23*
 Mercon V (XT-5-QM, XT-5-DM)**
 Mercon, Ford ESP-M2C166-H**
 Mercon SP, except 6HP26 / 6R60 / 6R75
 transmissions**
 XT-6-QSP, XT-6-DSP, except 6HP26 /
 6R60 / 6R75 transmissions**
 Mercon LV (XT-10-QLV)***
 Mitsubishi Diamond SP-II, SP-III, J2*
 Nissan Matic-D, J, K, 402*

Nissan Matic, J, S*
 Shell 3403, LA2634, Texaco 7045-E,
 ETL-8072B*
 Subaru ATF, ATF-HP*
 Toyota T-III, T-IV, WS, Ford XT8QAW*
 JWS 3309*
 Volvo Passenger Car (4 – 6 sp),
 Volvo 97340, 97341*
 VW G 052 025, 162, 099, 055 025*
 ZF TE-ML 02F, TE-ML 03D,
 TE-ML 04D, TE-ML 09, TE-ML 11A
 ZF TE-ML 14A, TE-ML 14B,
 TE-ML 14C, TE-ML 16L,
 ZF TE-ML 17C*
 VW TL52162 (LT71141)*

* Suitable for Use
 ** Vis Requirements not met
 *** Approved

TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	28.56
cSt @ 100°C	5.797
Viscosity Index	151
Pour Point, °F	-60
Specific Gravity @ 60°F (15.6°C)	0.8468
Gravity, °API	35.6
Color	Red