



Full Synthetic CVT Fluid

STARFIRE CHAIN & BELT FULL SYNTHETIC CVT FLUID is specially formulated with a unique combination of full synthetic base stocks and an advanced additive technology designed for the specific demands of CVTs. This premium-quality product is recommended for use in most belt or chain driven Continuously Variable Transmissions and it is not a replacement for ATF.

APPLICATIONS

Starfire Chain & Belt Full Synthetic CVT Fluid is suitable for use in the following applications:

Audi/VW (TL 52180; G 052 180; G 052 516)
BMW 8322 0 136 376/8322 0 429 154 (EZL799/EZL 799A)
Daihatsu Amix CVTF-DC, Daihatsu AMIX CVTF-DFE
Dodge/Jeep (NS-2 / CVTF+4/Mopar CVT 4)
Ford CFT30/WSS-M2C933-A/Motorcraft XT-7-QCFT
GM/Saturn (DEX-CVT, CVTF I-Green2)
Honda (HMMF, HCF-2)
Hyundai/Kia CVTF (SP-CVT 1)
Mazda CVTF 3320
Mercedes-Benz (236.20)
Mercedes-Benz CVT28/MB-Approval 236.20

Mini Cooper (EZL 799/EZL 799A/ZF CVT V1)
Mitsubishi (CVTF-J1)
Mitsubishi DiaQueen (CVTF-J1, CVTF-J4)
Nissan (NS-1, NS-2, NS-3)
Punch EZL 799/EZL 799A
Renault ELFMATIC
Shell Green 1V
Subaru (NS-2/Lineartronic CVTF, i-CVTF, K0425Y0710) e-CVTF
Suzuki (TC / NS-2/CVTF Green 1, CVTF Green 2, CVTF 3320)
Toyota (TC, FE)

TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	33.8
cSt @ 100°C	7.21
Viscosity Index	185
Pour Point, °F	-60
Specific Gravity @ 60°F (15.6°C)	0.8538
Gravity, °API	34.23
Color	Amber