



STARFIRE GL-1 Gear Lubricant

STARFIRE GL-1 Gear Lubricants are manufactured with high quality base stocks to provide outstanding oxidation stability for long service life. These oils are inhibited against foaming and does not contribute to corrosion or wear of yellow metals, such as brass or bronze.

FEATURES/BENEFITS:

- Long service life
- Non-foaming
- Non-corrosive

APPLICATIONS:

STARFIRE GL-1 Gear Lubricants are designed for use in manual transmissions and transfer cases in on-highway trucks and off-highway equipment, which require an API GL-1 gear lubricant. GL-1 Gear Lubricants are also suitable for use in industrial gear oil applications that call for a straight mineral oil in the SAE 50 engine oil viscosity weight range.

Typical Properties	Test Method	SAE 90	SAE 140
Gravity, °API	ASTM D287	28.99	26.69
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8817	0.8945
Viscosity @ 40°C cSt	ASTM D445	147.1	478.9
@ 100°C cSt	ASTM D445	14.89	30.08
Viscosity Index	ASTM D2270	101	98
Color	ASTM D1500	6.5	7.5

*** ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.**