



## METHYL ETHYL KETONE

Specific Gravity, 25°/25°C (D-268)	0.801 – 0.803
Specific Gravity, 20°/20°C (D-268)	0.805 – 0.807
Distillation, °C (D-1078)	
IBP	78.5 min
Dry Point	81.0 max
Acidity, % by wt, as Acetic Acid (D-1613)	0.005 max
Purity, % by wt (D-2804)	99.5 min
Water, % by wt (D-1364)	0.10 max
Nonvolatile, mg/100 ml (D-1343)	5 max
Color, Pt-Co (D-1209)	10 max
<b>Shipping Data:</b>	
Pounds per Gallon, 20°C	6.71
Kg per Liter, 20°C	0.81
Flash Point, °F (T.C.C.)	24 (-4°C)
DOT Label Required	Flammable Liquid
DOT Identification No.	UN 1193

Methyl Ethyl Ketone sales specifications can comply with but are not certified to the following specifications:

ASTM D-740, Methyl Ethyl Ketone, Type I (Regular)

**Code:** 20019 (BULK)

**C.A.S. No.:** 78-93-3

( ) Indicates ASTM Test Method  
1408

NOTICE: Coolants Plus makes no warranty or representation as to the suitability of the product as specified herein for any particular application. The determination of the suitability of the above specification for any particular use is solely the responsibility of the user.

All precautionary labels and notices should be read and understood by all supervisory personnel and employees before using. Consult Coolants Plus and OSHA regulations for additional safety and health information. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product. Special attention should be given to consumer applications.