



MERCON® V ATF

STARFIRE MERCON® V ATF is specially formulated with a unique combination of conventional base stocks and advanced additive technology to meet performance requirements of Ford automatic transmissions calling for MERCON® V fluid. Not for use in transmissions requiring Ford Type F fluid or Continuous Variable Transmissions (CVTs).

STARFIRE MERCON® V ATF is suitable for use where the following automatic transmission fluids are recommended: automobile and truck automatic transmissions, power-shift transmissions and other types of service requiring an approved and Ford Mercon® V automatic transmission fluid. Dexron®-III (G, H), II (E, F) specifications, Honda Z-1, Nissan Matic-J and Toyota T-IV.

CLAIMS INFORMATION

Allison C-4***

Allison TES-389*

Audi G 052 025, 052 162, 055 025*

Esso 71141*

BMW P/N 83 22 0 024 359, ETL-8072B*

BMW P/N 83 22 0 0246 922, ETL-7045E*

BMW P/N 83 22 0 403 249, ETL-8072B*

BMW P/N 83 22 9 407 765, LA 2634*

BMW P/N 83 22 9 407 807, LT 711 41*

BMW 7045E, LA2634, LT71141*

Dexron III G/H, Dexron II,

Dexron, AW1*

Honda DW-1, Z-1*

Volvo P/N 1161540-8*

Hyundai/Kia/Mitsubishi Diamond

SP-II and SP-III, RED-1, SP-IV*

Chrysler AS68RC, Diamond SP-III*

Idemitsu K17*

JWS 3309, Any 3309*

M315-2004 JASO 1A, 2A***

MAN 339 Type Z1, Z2, V1**

Mazda ATF M-III, MV, T-IV*

MB236.1,2,5,6,7,9, 10, 11*

Suzuki 3314, 3317*

Ford P/N XT-2-DX (MERC),

Ford P/N XT-2-SM (SYN MERC)*

Mercon V (XT-5-QM, XT-5-DM)***

Mercon, Ford ESP-M2C166-H*

Nissan Matic-D, J, K, 402*

Texaco N402*

Shell 3403, LA2634,

Texaco 7045-E, ETL-8072B*

Hyundai NSWS9638*

Fuchs 3353*

IDEMITSU APOROIL ATF HP*

ISUZU 08200-9001 / Genuine ATF*

MINI P/N 83 22 0 402 413*

Saturn P/N 21005966*

SAAB P/N 22 717 466, 93 165 147 (AW-1)*

Jaguar P/N WSS-M2C922-A-1*

Porsche P/N 999 917 547 00 (A2)*

VW P/N GUS 000 162*

Shell ATF 134, 3353, 3403 M115*

Subaru ATF, ATF-HP*

Toyota T-II, T-III, T-IV, WS, Ford XT8QAW*

Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF*

JWS 3324*

Voith 55.6335 (G607)*

Volvo Passenger Car (4 – 6 sp),

Volvo 97340, 97341)*

VW G 052 025, 162, 099, 055 025*

ZF TE-ML 03D, 04D, 05L, 09, 11B,

14A, 16L, 17C, ZF TE-ML 14B

* Suitable for Use

** Meets Requirements

*** Approved

TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	35.43
cSt @ 100°C	7.56
cP @ -40°C, max.	13000
Viscosity Index, min.	189
Flash, COC, °F	390
Pour Point, °F	-60
Specific Gravity @ 60°F	0.8601
API Gravity	33.02
Color	Red