



ODORLESS MINERAL SPIRITS

Typical Properties:

	Specifications	Typical
Color, Pt-Co (D-1209)	0.740 – 0.775	0.7603
Flash Point, °F (D-56)	30 min	+30
Kauri-Butanol Value (D-1133)		< 15
Corrosion (D-130)	110 min (43°C)	124 (51°C)
Distillation, °F (D-86) Dry Point		28 1A
Aromatic Content	340 min (171.0 °C) 410 max (210.0°C)	347 (175.0 °C) 392 (200.0 °C) < 0.25 vol%

Shipping Data:

Pounds Per Gallon, 60°F (15.6°C)	6.33
Kg per Liter, 60°F (15.6°C)	0.76
Flash Point, °F (T.C.C.)	124 (51°C)
DOT Label Required	None
DOT Identification No.	UN 1268

Odorless Mineral Spirits meets the following specifications:

ASTM D-235 (Type III) Mineral Spirits

TT-T-291F (Type III) Thinner, Paint, Mineral Spirits, Regular and Odorless (S/S by A-A-2904)

A-A-2904 Thinner, Paint, Mineral Spirits, Regular and Odorless (S/S by MIL-PRF-680C)

MIL-PRF-680C (Type I) Degreasing Solvent, Mineral Spirits, Low Flash Point